

WAKOL RL 1805 PU-Adhesive Remover

Product Data Sheet

Description

Cleaning agent for removing cured polyurethane adhesive residue from finished wood flooring surfaces.

Special Features

- Very low odor
- Easy to spread
- High efficiency
- Also removes persistent stains of PU-adhesives

Properties

Base: Organic solvent
Shelf life: approx. 24 month in unopened container at 70 °F

Application

With brush directly on residue

Use

Since wood floor finishes differ in their chemical stability, first test on an unused board or out of the way area of the floor to ensure that WAKOL RL 1805 PU Adhesive Remover does not affect the finish. Test by dropping WAKOL RL 1805 on the finish and evaluate the surface after 60 minutes. The treated area of the finish must show no clouding, swelling, softening or other damage.

Apply WAKOL RL 1805 PU-Adhesive Remover to cured adhesive residue with a brush. Depending on the level of curing of the adhesive, wait between 30 minutes and 12 hours. Fingerprints of cured adhesive (within 24 hours after applying), usually take just 30 to 60 minutes to be softened and ready for removal. Remove the softened adhesive with a plastic trowel or putty knife; metal tools will scratch the finish. If necessary, repeat procedure. Finally, clean off with a moist cloth and mild wood floor cleaner.

General Information

Do not use WAKOL RL 1805 PU-Adhesive Remover below grade with excessive moisture or hydrostatic pressure. Acclimatize materials during cold periods properly.

Disclaimer

The responsibility of the suitability of the adhesive for each individual case cannot be assumed, as the manufacturer has no influence on the proper application of the adhesives by the installer and or contractor. The directions for use were established on the basis of research, experience and tests believed reliable. Any liability on the part of the seller cannot be derived therefrom, verbal information is subject to written confirmation.