Printing date 10/19/2023

Reviewed on 10/19/2023

1 Identification

· Product identifier

• Trade name: <u>WAKOL D 3120 LVT/LVP Adhesive</u>

· Application of the substance / the mixture Adhesives

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Loba-Wakol, LLC 2732 Hwy 74 West Wadesboro, NC 28170, USA info@loba-wakol.com +1 704 527 5919

· Information department: Product safety department.

• Emergency telephone number: Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or International (001) 352 323 3500

2 Hazard(s) identification

Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH 0	Health = 0
FIRE 0	Fire = 0
REACTIVITY 0	<i>Reactivity</i> $= 0$

• Other hazards

- · Results of PBT and vPvB assessment
- · *PBT:* Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- **Description:** Adhesive

· Dangerous components:

 >0.25–≤1%

(Contd. on page 2)

- US



Printing date 10/19/2023

Reviewed on 10/19/2023

(Contd. of page 1)

 $>0.25 - \le 1\%$

Trade name: WAKOL D 3120 LVT/LVP Adhesive

1310-73-2 sodium hydroxide

Corrosive to Metals 1, H290; Skin Corrosion 1A, H314

4 First-aid measures

- · Description of first aid measures
- General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- *After swallowing:* Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- Environmental precautions:

Do not allow product to reach sewage system or any water course. Dilute with plenty of water.

- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· PAC-1:

577-11-7 Dioctyl sulfosuccinatesodium salt: 5.7 mg/m³

1310-73-2 sodium hydroxide: 0.5 mg/m³

• **PAC-2:**

577-11-7 Dioctyl sulfosuccinatesodium salt: 63 mg/m³

1310-73-2 sodium hydroxide: 5 mg/m³

(Contd. on page 3)





Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: WAKOL D 3120 LVT/LVP Adhesive

· PAC-3:

577-11-7 Dioctyl sulfosuccinatesodium salt: 380 mg/m³

1310-73-2 sodium hydroxide: 50 mg/m³

7 Handling and storage

· Handling:

- *Precautions for safe handling* No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from frost.

Store in cool, dry conditions in well sealed receptacles. • Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed.
- Wash hands before breaks and at the end of work.
- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

• Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)



(Contd. of page 2)

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: WAKOL D 3120 LVT/LVP Adhesive

 $(Contd. \ of \ page \ 3)$

• *Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*

• Eye protection:

Safety glasses

L

· Body protection: Protective work clothing

	ical properties
 Information on basic physical and chemical properties General Information Appearance: 	
Color: V • Odor: Color:	Pasty White Characteristic Not determined.
• <i>pH-value at 20 °C (68 °F):</i> 7	7.8
	Undetermined. 100 °C (212 °F)
• Flash point: N	Not applicable.
• Flammability (solid, gaseous):	Not applicable.
• Decomposition temperature: N	Not determined.
• Ignition temperature: F	Product is not selfigniting.
• Danger of explosion: H	Product does not present an explosion hazard.
	Not determined. Not determined.
· Vapor pressure at 20 °C (68 °F): 2	23 hPa (17.3 mm Hg)
Relative densityNVapor densityN	1.03 g/cm³ (8.595 lbs/gal) (EN ISO 2811-1) Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water: F	Fully miscible.
• Partition coefficient (n-octanol/water): N	Not determined.
Kinematic: N	86,000 mPas (ISO 2555) Not determined. 0.0 % (Contd. on page 5)





Printing date 10/19/2023

Anspruch verbin

Reviewed on 10/19/2023

Trade name: WAKOL D 3120 LVT/LVP Adhesive

(Contd. of page 4)

VOC content: Solids content: 0.0 %

• Other information

No further relevant information available.

61.3 % (DIN EN 827.8.2)

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- $\cdot \textit{Incompatible materials: } No further relevant information available.$
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

• Information on toxicological effects

• Acute toxicity:

• *LD/LC50* values that are relevant for classification:

2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral LD50 1,193 mg/kg (rat)

Dermal LD50 4,115 mg/kg (rat)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H - isothiazol-3-one [EC No 220-239-6] (3:1)

Oral LD50 66 mg/kg (rat)

Dermal LD50 141 mg/kg (rat)

• Primary irritant effect:

• on the skin: No irritant effect.

• on the eye:

No irritating effect.

Based on available data, the classification criteria are not met.

· Sensitization: No sensitizing effects known.

• Additional toxicological information: The product is not subject to classification according to internally approved calculation methods for preparations:

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 6)

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: WAKOL D 3120 LVT/LVP Adhesive

(Contd. of page 5) 12 Ecological information · Toxicity • Aquatic toxicity: 2634-33-5 1,2-benzisothiazol-3(2H)-one LC50/96h 2.18 mg/l (Oncorhynchus mykiss) 2.2 mg/l (Lepomis macrochirus) EC50/18h 0.4 mg/l (Pseudomonas putida) EC50/48h 2.94 mg/l (Daphnia magna) EC50/72h 0.067 mg/l (Pseudokirchneriella subcapitata) EC01 mg/l (Daphnia magna) 55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H isothiazol-3-one [EC No 220-239-6] (3:1) NOEC/48h 0.00064 mg/l (Skeletonema costatum) NOEC/21d 0.004 mg/l (Daphnia magna) LC50/96h 0.188 mg/l (Oncorhynchus mykiss) *EC20/3h* 0.97 mg/l (sludge) EC50/48h 0.126 mg/l (Daphnia magna) EC50/3h 7.92 mg/l (sludge) (OECD 209) EC50/72h 0.048 mg/l (Pseudokirchneriella subcapitata) EC50/96h 0.22 mg/l (Oncorhynchus mykiss) NOEC/72h 0.0012 mg/l (Pseudokirchneriella subcapitata) · Persistence and degradability No further relevant information available. · Behavior in environmental systems: · Bioaccumulative potential No further relevant information available. · Mobility in soil No further relevant information available. • Additional ecological information: · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Smaller quantities can be disposed of with household waste.
- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*
- Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 7)



Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: WAKOL D 3120 LVT/LVP Adhesive

(Contd. of page 6)

4 Transport information	
· UN-Number	
• DOT, ADR, ADN, IMDG, IATA • UN proper shipping name	Void
· DOT, ADR, ADN, IMDG, IATA	Void
• Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	¥7 . 1
DOT, ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
• Special precautions for user	Not applicable.
• Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
·DOT	
· Remarks:	not regulated
· ADR	
· Remarks:	not regulated
·IMDG	
· Remarks:	not regulated
·IATA	
· Remarks:	not regulated
• UN "Model Regulation":	Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara
- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):
- None of the ingredients is listed.
- TSCA (Toxic Substances Control Act):
- All ingredients are listed or are not required to be listed on the TSCA inventory.

· Hazardous Air Pollutants

- None of the ingredients is listed.
- · Proposition 65
- · Chemicals known to cause cancer:
- None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for females:
- None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:
- None of the ingredients is listed.

(Contd. on page 8)



⁻US-

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: WAKOL D 3120 LVT/LVP Adhesive

(Contd. of page 7)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

1310-73-2 sodium hydroxide

· New Jersey Special Hazardous Substance List:

- 1310-73-2 sodium hydroxide: CO, R1 · Pennsylvania Right-to-Know List:
- 1310-73-2 sodium hydroxide · Pennsylvania Special Hazardous Substance List:
- 1310-73-2 sodium hvdroxide: E
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void

· National regulations:

- · VOC:
- VOC (EU) 0.7 g/l
- VOC (USA): 0.4 g/l / 0.00 lb/gal
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. · Contact: · Date of preparation / last revision 10/19/2023 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Corrosive to Metals 1: Corrosive to metals - Category 1 Skin Corrosion 1A: Skin corrosion/irritation - Category 1A

(Contd. on page 9)

Ansnruch verbin



Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: WAKOL D 3120 LVT/LVP Adhesive

Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation – Category 1 (Contd. of page 8)

- US –