

Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WAKOL GmbH Bottenbacher Str. 30 D-66954 Pirmasens info@wakol.com +49 6331 8001 0

· Informing department:

Product safety department. msds@wakol.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Contains a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive
- · Dangerous components:

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

< 0.05%

H317

Specific concentration limit: Skin Sens. 1; H317: $C \ge 0.05$

%

(Contd. on page 2)



Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 1)

CAS: 55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC \geq 0.00025-<0.0015%

EC number: 611-341-5 No 247-500-7] and 2-methyl-2 H-isothiazol-3-one [EC No

220-239-6] (3:1)

Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318;

♦ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ♠ Skin Sens. 1A, H317, EUH071

Specific concentration limits:

Skin Corr. 1C; H314: C ≥0.6 %

Skin Irrit. 2; H315: $0.06 \% \le C < 0.6 \%$

Eye Dam. 1; H318: $C \ge 0.6 \%$

Eye Irrit. 2; H319: $0.06 \% \le C < 0.6 \%$ Skin Sens. 1A; H317: $C \ge 0.0015 \%$

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one <0.0015%

(1) Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1,

H410 (M=1); (1) Skin Sens. 1A, H317, EUH071

Specific concentration limit: Skin Sens. 1A; H317: $C \ge 0.0015$

0.0015 %

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

(Contd. on page 3)



Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 2)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Dilute with plenty of water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

2634-33-5 1,2-benzisothiazol-3(2H)-one

Dermal DNEL 0.345 mg/kg/day (conmsumer (long-term))

0.966 mg/kg/day (workwr (long-term))

Inhalative DNEL 1.2 mg/m³ (conmsumer (long-term))

6.81 mg/m³ (workwr (long-term))

· PNECs

2634-33-5 1,2-benzisothiazol-3(2H)-one

PNEC 4.03 µg/l (freshwater)

0.403 μg/l (sea water)

PNEC 1.03 mg/l (purification plant)

PNEC 3 mg/kg (soil)

0.00499 mg/kg (sediment (sea water))

0.0499 mg/kg (sediment (freshwater))

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)



Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 3)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Hand protection



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: White

· Smell: Characteristic
· Odour threshold: Not determined.

· Melting point/freezing point: $0 \, {}^{\circ}C$

· Boiling point or initial boiling point and boiling

range 100 °C

· Flammability Not applicable.

· Lower and upper explosion limit

Lower:

Upper:
Not determined.
Flash point:
Decomposition temperature:
Not applicable.
Not determined.
Not determined.
Not determined.
Not determined.
7.8 (ISO 976)

· Viscosity:

· Kinematic viscosity Not determined.

(Contd. on page 5)



Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 4)

· kinematic (calculated) at 40°C:

· dynamic at 20 °C: 61,000 mPas (ISO 2555)

·Solubility

· Water: Fully miscible. Not determined. · Partition coefficient n-octanol/water (log value) · Steam pressure at 20 °C: 23 hPa

· Density and/or relative density

1.4 g/cm³ (EN ISO 2811-1) · Density at 20 °C

· Relative density Not determined. · Vapour density Not determined.

9.2 Other information

· Appearance:

· Form: Pasty

Important information on protection of health and

environment, and on safety.

Self-inflammability: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

 \cdot VOC 0.00 %

· Solids content: 77.0 % (DIN EN 827.8.2)

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Void · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral LD50 1,193 mg/kg (rat)

Dermal LD50 4,115 mg/kg (rat)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

Oral LD50 66 mg/kg (rat)

Dermal LD50 141 mg/kg (rat)

2682-20-4 2-methyl-2H-isothiazol-3-one

Oral LD50 285 mg/kg (rat)

Dermal LD50 > 2,000 mg/kg (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity } \textit{Based on available data, the classification criteria are not met.}$
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

2634-33-5 1,2-benzisothiazol-3(2H)-one

LC50/96h 2.18 mg/l (Oncorhynchus mykiss)

2.2 mg/l (Lepomis macrochirus)

EC50/18h 0.4 mg/l (Pseudomonas putida)

EC50/48h 2.94 mg/l (Daphnia magna)

EC50/72h 0.067 mg/l (Pseudokirchneriella subcapitata)

EC0 1 mg/l (Daphnia magna)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

NOEC/48h 0.00064 mg/l (Skeletonema costatum)

(Contd. on page 7)



Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 6)

NOEC/21d 0.004 mg/l (Daphnia magna)

LC50/96h 0.188 mg/l (Oncorhynchus mykiss)

EC20/3h 0.97 mg/l (sludge)

EC50/48h 0.126 mg/l (Daphnia magna)

EC50/3h 7.92 mg/l (sludge) (OECD 209)

EC50/72h 0.048 mg/l (Pseudokirchneriella subcapitata)

EC50/96h 0.22 mg/l (Oncorhynchus mykiss)

NOEC/72h 0.0012 mg/l (Pseudokirchneriella subcapitata)

2682-20-4 2-methyl-2H-isothiazol-3-one

LC50/96h 0.6 mg/l (Oncorhynchus mykiss)

12.4 mg/l (Lepomis macrochirus)

EC50/18h 2.3 mg/l (Pseudomonas putida)

EC50/48h 1.6 mg/l (Daphnia magna)

EC50/72h 0.157 mg/l (Pseudokirchneriella subcapitata)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

(Contd. on page 8)



Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class

· 14.4 Packing group · ADR, IMDG, IATA

Void

Void

· ADK, IMDG, IATA · 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user

Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

· UN "Model Regulation": Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · GEV-Guidline/EMICODE: EC 1 plus, "very low emission"
- · VOC (EU) 0.0 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- *H410 Very toxic to aquatic life with long lasting effects.*

EUH071 Corrosive to the respiratory tract.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

(Contd. on page 9)





Printing date 15.06.2023 Version number 1 Revision: 15.06.2023

Trade name: WAKOL D 3316 PVC Adhesive, fibre-containing

(Contd. of page 8)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

- GB