

Printing date 10/25/2023 Reviewed on 10/25/2023

# 1 Identification

- · Product identifier
- · Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible
- · Application of the substance / the mixture Adhesives
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Loba-Wakol, LLC 2732 Hwy 74 West Wadesboro, NC 28170, USA info@loba-wakol.com +1 704 527 5919

- · Information department: Product safety department.
- · Emergency telephone number:

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or

International (001) 352 323 3500

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

· Hazard statements

Suspected of damaging fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 0Reactivity = 0

(Contd. on page 2)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Adhesive
- · Dangerous components:

52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

>0.1-\(\leq 0.25\)%

**♦** Toxic to Reproduction 2, H361; **♦** Eye Damage 1, H318

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 2)

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:

471-34-1 calcium carbonate: 45 mg/m<sup>3</sup>

25322-69-4 Propylene Glycol: 30 mg/m<sup>3</sup>

· *PAC-2*:

471-34-1 calcium carbonate: 210 mg/m<sup>3</sup>

25322-69-4 Propylene Glycol: 330 mg/m<sup>3</sup>

· *PAC-3*:

471-34-1 calcium carbonate: 1,300 mg/m<sup>3</sup>

25322-69-4 Propylene Glycol: 2,000 mg/m³

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling Use only in well ventilated areas.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Protect from humidity and water.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information:

The lists that were valid during the creation were used as basis.

See Section 10.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

· Breathing equipment: Not necessary if room is well-ventilated.

(Contd. on page 4)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 3)

### · Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.35$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Pasty

Color: Cream colored
Odor: Odorless
Odor threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.
Undetermined.

Not applicable.

Flammability (solid, gaseous):

Decomposition temperature:
Not determined.

· Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

Vapor pressure: Not determined.

(Contd. on page 5)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 4)

• **Density at 20 °C (68 °F):** 1.84 g/cm³ (15.355 lbs/gal) (EN ISO 2811-1)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic at 20 °C (68 °F):** 80,000 mPas (ISO 2555)

**Kinematic:** Not determined.

Organic solvents: 0.1 % VOC content: 0.1 %

**Solids content:** 95.0 % (DIN EN 827.8.2)

• Other information No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- · Conditions to avoid No further relevant information available.
- $\cdot \textit{Incompatible materials:} \ \textit{No further relevant information available}.$
- · Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information: Product releases low quantities of methanol during appropiated application.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

### 52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

Oral LD50 3,700 mg/kg (rat)

Dermal LD50 3,170 mg/kg (rat)

- · Primary irritant effect:
- on the eye: Based on available data, the classification criteria are not met.
- · Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 6)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 5)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### 52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

NOEC/21d (static) 0.23 mg/l (Daphnia magna) (OECD RL 211)

LC50/96h 4.4 mg/l (Leuciscus macrochirus) (OECD RL 203) EC50/48h 8.6 mg/l (Daphnia magna) (OECD RL 202 T1)

EC50/3h >100 mg/l (sludge) (OECD RL 209)

EC50/72h 0.705 mg/l (Scenedesmus subspicatus) (RL 92/69/EWG, C.3)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Void

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Void

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Void

· Packing group

· **DOT**, **ADR**, **IMDG**, **IATA** Void

(Contd. on page 7)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 6)

· Environmental hazards:

· Marine pollutant:

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

 $\cdot DOT$ 

· Remarks: not regulated

 $\cdot ADR$ 

· Remarks: not regulated

 $\cdot$  *IMDG* 

· Remarks: not regulated

 $\cdot$  IATA

· Remarks: not regulated

· UN "Model Regulation": Void

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed or are not required to be listed on the TSCA inventory.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

1317-65-3 limestone

· New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

Pennsylvania Right-to-Know List:

1317-65-3 limestone

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

(Contd. on page 8)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 7)

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



### · Signal word Warning

### · Hazard-determining components of labeling:

Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

· Hazard statements

Suspected of damaging fertility or the unborn child.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

- · VOC:
- · **VOC (EU)** 1.0 g/l
- · **VOC (USA):** 1.0 g/l / 0.01 lb/gal
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child.

- · Contact:
- · Date of preparation / last revision 10/25/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 9)





Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 228 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 8)

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit
Eye Damage 1: Serious eye damage/eye irritation – Category 1
Toxic to Reproduction 2: Reproductive toxicity – Category 2