

Printing date 10/25/2023 Reviewed on 10/25/2023

1 Identification

- · Product identifier
- · Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible
- · Application of the substance / the mixture Adhesives
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Loba-Wakol, LLC 2732 Hwy 74 West Wadesboro, NC 28170, USA info@loba-wakol.com +1 704 527 5919

- · Information department: Product safety department.
- · Emergency telephone number:

Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or

International (001) 352 323 3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

· Hazard statements

Suspected of damaging fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 0Reactivity = 0

(Contd. on page 2)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Adhesive
- · Dangerous components:

52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

>0.1-≤0.25%

♦ Toxic to Reproduction 2, H361; **♦** Eye Damage 1, H318

13822-56-5 3-(trimethoxysilyl)propylamine

>0.1-<0.25%

Eye Damage 1, H318; Skin Irritation 2, H315; Flammable Liquids 4, H227

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

(Contd. on page 3)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 2)

- Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:

471-34-1 calcium carbonate: 45 mg/m³

25322-69-4 Propylene Glycol: 30 mg/m³

13822-56-5 3-(trimethoxysilyl)propylamine: 30 mg/m³

20344-49-4 iron hydroxide oxide: 24 mg/m³

· *PAC-2*:

471-34-1 calcium carbonate: 210 mg/m³

25322-69-4 Propylene Glycol: 330 mg/m³

13822-56-5 3-(trimethoxysilyl)propylamine: 330 mg/m³

20344-49-4 iron hydroxide oxide: 260 mg/m³

· *PAC-3*:

471-34-1 calcium carbonate: 1,300 mg/m³

25322-69-4 Propylene Glycol: 2,000 mg/m³

13822-56-5 3-(trimethoxysilyl)propylamine: 2,000 mg/m³

20344-49-4 iron hydroxide oxide: $1,600 \text{ mg/m}^3$

7 Handling and storage

- · Handling:
- Precautions for safe handling Use only in well ventilated areas.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 4)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 3)

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists that were valid during the creation were used as basis.

See Section 10.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Color:
Codor:
Codor:
Codor threshold:
Pasty
Color
Codorless
Not determined.
Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

(Contd. on page 5)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 4)

Boiling point/Boiling range: Undetermined.

Flash point: Not applicable.

Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

• Vapor pressure: Not determined.

• **Density at 20 °C (68 °F):** 1.80 g/cm³ (15.021 lbs/gal) (EN ISO 2811-1)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 600,000 mPas (ISO 2555)

Kinematic: Not determined.

Organic solvents: 0.1 % VOC content: 0.1 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information: Product releases low quantities of methanol during appropiated application.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

Oral LD50 3,700 mg/kg (rat) Dermal LD50 3,170 mg/kg (rat)

(Contd. on page 6)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 5)

- · Primary irritant effect:
- · on the eye: Based on available data, the classification criteria are not met.
- · Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

NOEC/21d (static) 0.23 mg/l (Daphnia magna) (OECD RL 211)

LC50/96h 4.4 mg/l (Leuciscus macrochirus) (OECD RL 203) EC50/48h 8.6 mg/l (Daphnia magna) (OECD RL 202 T1)

EC50/3h >100 mg/l (sludge) (OECD RL 209)

EC50/72h 0.705 mg/l (Scenedesmus subspicatus) (RL 92/69/EWG, C.3)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

ıs -



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 6)

14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA

Void

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA

Void

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class

Void

· Packing group

· DOT, ADR, IMDG, IATA

Void

Environmental hazards:Special precautions for user

Not applicable. Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

Not dangerous according to the above specifications.

 $\cdot DOT$

· Remarks:

not regulated

 $\cdot ADR$

· Remarks:

not regulated

· IMDG

Remarks:

not regulated

 \cdot IATA

· Remarks:

not regulated

· UN "Model Regulation":

Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed or are not required to be listed on the TSCA inventory.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 8)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 7)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

1317-65-3 limestone

· New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

· Pennsylvania Right-to-Know List:

1317-65-3 limestone

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

· Hazard statements

Suspected of damaging fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · VOC:
- VOC (EU) 1.4 g/l
- · **VOC (USA):** 1.4 g/l / 0.01 lb/gal
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H227 Combustible liquid.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child.

- · Contact:
- · Date of preparation / last revision 10/25/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 9)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL MS 232 Wood Flooring Adhesive, flexible

(Contd. of page 8)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation – Category 1

Toxic to Reproduction 2: Reproductive toxicity – Category 2

- US