

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

1 Identification

- **Product identifier**
- **Trade name:** *WAKOL MS 292 Wood Flooring Adhesive, firm*
- **Application of the substance / the mixture** *Adhesives*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Loba-Wakol, LLC
2732 Hwy 74 West
Wadesboro, NC 28170, USA
info@loba-wakol.com
+1 704 527 5919*
- **Information department:** *Product safety department.*
- **Emergency telephone number:**
*Emergency CONTACT (24-Hour-Number)
GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or
International (001) 352 323 3500*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS08

- **Signal word** *Warning*
- **Hazard statements**
Suspected of damaging fertility or the unborn child.
- **Precautionary statements**
*Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.
IF exposed or concerned: Get medical advice/attention.
Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



*Health = 0
Fire = 1
Reactivity = 0*

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: **WAKOL MS 292 Wood Flooring Adhesive, firm**

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Adhesive**
- **Dangerous components:**

52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate	>0.1–≤0.25%
⚠ Toxic to Reproduction 2, H361; ⚠ Eye Damage 1, H318	
13822-56-5 3-(trimethoxysilyl)propylamine	>0.1–≤0.25%
⚠ Eye Damage 1, H318; ⚠ Skin Irritation 2, H315; Flammable Liquids 4, H227	

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 292 Wood Flooring Adhesive, firm

(Contd. of page 2)

- **Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

· **PAC-1:**

471-34-1 calcium carbonate: 45 mg/m³

13822-56-5 3-(trimethoxysilyl)propylamine: 30 mg/m³

20344-49-4 iron hydroxide oxide: 24 mg/m³

· **PAC-2:**

471-34-1 calcium carbonate: 210 mg/m³

13822-56-5 3-(trimethoxysilyl)propylamine: 330 mg/m³

20344-49-4 iron hydroxide oxide: 260 mg/m³

· **PAC-3:**

471-34-1 calcium carbonate: 1,300 mg/m³

13822-56-5 3-(trimethoxysilyl)propylamine: 2,000 mg/m³

20344-49-4 iron hydroxide oxide: 1,600 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Use only in well ventilated areas.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:**
The lists that were valid during the creation were used as basis.
See Section 10.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 292 Wood Flooring Adhesive, firm

(Contd. of page 3)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not necessary if room is well-ventilated.
- **Protection of hands:**



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

- **Material of gloves**
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.35 mm
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Pasty
Color:	Light brown
Odor:	Odorless
Odor threshold:	Not determined.
pH-value:	Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
- **Flash point:** >200 °C (>392 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Decomposition temperature:** Not determined.
- **Ignition temperature:** Product is not selfigniting.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 292 Wood Flooring Adhesive, firm

(Contd. of page 4)

- **Danger of explosion:** *Product does not present an explosion hazard.*
- **Explosion limits:**
 - **Lower:** *Not determined.*
 - **Upper:** *Not determined.*
- **Vapor pressure:** *Not determined.*
- **Density at 20 °C (68 °F):** *1.79 g/cm³ (14.938 lbs/gal) (EN ISO 2811-1)*
- **Relative density** *Not determined.*
- **Vapor density** *Not determined.*
- **Evaporation rate** *Not determined.*
- **Solubility in / Miscibility with Water:** *Not miscible or difficult to mix.*
- **Partition coefficient (n-octanol/water):** *Not determined.*
- **Viscosity:**
 - **Dynamic at 20 °C (68 °F):** *650,000 mPas (ISO 2555)*
 - **Kinematic:** *Not determined.*
 - **Organic solvents:** *0.1 %*
 - **VOC content:** *0.1 %*
- **Other information** *No further relevant information available.*

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*
- **Additional information:** *Product releases low quantities of methanol during appropriated application.*

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

 - 52829-07-9 **Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate**
 - Oral LD50 3,700 mg/kg (rat)
 - Dermal LD50 3,170 mg/kg (rat)
- **Primary irritant effect:**
- **on the eye:** *Based on available data, the classification criteria are not met.*
- **Additional toxicological information:**

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 292 Wood Flooring Adhesive, firm

(Contd. of page 5)

- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
None of the ingredients is listed.
- **NTP (National Toxicology Program)**
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate
NOEC/21d (static) 0.23 mg/l (*Daphnia magna*) (OECD RL 211)
LC50/96h 4.4 mg/l (*Leuciscus macrochirus*) (OECD RL 203)
EC50/48h 8.6 mg/l (*Daphnia magna*) (OECD RL 202 T1)
EC50/3h >100 mg/l (sludge) (OECD RL 209)
EC50/72h 0.705 mg/l (*Scenedesmus subspicatus*) (RL 92/69/EWG, C.3)
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, ADN, IMDG, IATA** Void

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 292 Wood Flooring Adhesive, firm

(Contd. of page 6)

- **UN proper shipping name** Void
- **DOT, ADR, ADN, IMDG, IATA** Void
- **Transport hazard class(es)**
- **DOT, ADR, ADN, IMDG, IATA**
- **Class** Void
- **Packing group**
- **DOT, ADR, IMDG, IATA** Void
- **Environmental hazards:** Not applicable.
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:** Not dangerous according to the above specifications.
- **DOT**
- **Remarks:** not regulated
-
- **ADR**
- **Remarks:** not regulated
-
- **IMDG**
- **Remarks:** not regulated
-
- **IATA**
- **Remarks:** not regulated
- **UN "Model Regulation":** Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
None of the ingredients is listed.
- **TSCA (Toxic Substances Control Act):**
All ingredients are listed or are not required to be listed on the TSCA inventory.
- **Hazardous Air Pollutants**
None of the ingredients is listed.
- **Proposition 65**
- **Chemicals known to cause cancer:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.
- **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.
- **New Jersey Right-to-Know List:**
1317-65-3 limestone

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 292 Wood Flooring Adhesive, firm

(Contd. of page 7)

· **New Jersey Special Hazardous Substance List:**

None of the ingredients is listed.

· **Pennsylvania Right-to-Know List:**

1317-65-3 limestone

· **Pennsylvania Special Hazardous Substance List:**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS08

· **Signal word** Warning

· **Hazard statements**

Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **VOC:**

· **VOC (EU)** 1.5 g/l

· **VOC (USA):** 1.5 g/l / 0.01 lb/gal

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H227 Combustible liquid.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child.

· **Contact:**

· **Date of preparation / last revision** 10/25/2023

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 292 Wood Flooring Adhesive, firm

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Toxic to Reproduction 2: Reproductive toxicity – Category 2

US