Printing date 10/25/2023

1 Identification

· Product identifier

• Trade name: <u>WAKOL MS 230 Wood Flooring Adhesive, flexible</u> • Application of the substance / the mixture Adhesives

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Loba-Wakol, LLC 2732 Hwy 74 West Wadesboro, NC 28170, USA info@loba-wakol.com +1 704 527 5919

· Information department: Product safety department.

• Emergency telephone number: Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or International (001) 352 323 3500

2 Hazard(s) identification

```
Classification of the substance or mixture
GHS08 Health hazard
Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.
Label elements
GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
Hazard pictograms
GHS08
Signal word Warning
```

· Hazard-determining components of labeling:

Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate • Hazard statements

Suspected of damaging fertility or the unborn child.

• Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)

1 0 Health = 0Fire = 1 Reactivity = 0

(Contd. on page 2)

Reviewed on 10/25/2023

⁻ US



Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible

(Contd. of page 1)

>0.1-≤0.25%

>0.1-<0.25%

HMIS-ratings (scale 0 - 4)
HEALTH Health = 0 FIRE 1 Fire = 1 REACTIVITY Reactivity = 0
Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients
• Chemical characterization: Mixtures

• Description: Adhesive

· Dangerous components:

13822-56-5 3-(trimethoxysilyl)propylamine

🔶 Eye Damage 1, H318; 🚸 Skin Irritation 2, H315; Flammable Liquids 4, H227

4 First-aid measures

· Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.

- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.

• Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation* • *Environmental precautions:* Do not allow product to reach sewage system or any water course.

(Contd. on page 3)





Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible

(Contd. of page 2) • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · PAC-1: 471-34-1 calcium carbonate: 45 mg/m³ 25322-69-4 Propylene Glycol: 30 mg/m³ 13822-56-5 3-(trimethoxysilyl)propylamine: 30 mg/m³ 20344-49-4 iron hydroxide oxide: 24 mg/m³ • PAC-2: 471-34-1 calcium carbonate: 210 mg/m³ 25322-69-4 Propylene Glycol: 330 mg/m³ 13822-56-5 3-(trimethoxysilyl)propylamine: 330 mg/m³ 20344-49-4 iron hydroxide oxide: 260 mg/m³ **PAC-3**: 471-34-1 calcium carbonate: 1,300 mg/m³ 25322-69-4 Propylene Glycol: 2,000 mg/m³ 13822-56-5 3-(trimethoxysilyl)propylamine: 2,000 mg/m³ 20344-49-4 iron hydroxide oxide: 1,600 mg/m³

7 Handling and storage

· Handling:

- Precautions for safe handling Use only in well ventilated areas.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Protect from humidity and water.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 4)



Printing date 10/25/2023

Printing date 10/25/2023

Anspruch verb

Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible

(Contd. of page 3)

- Control parameters
 Components with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- *Additional information: The lists that were valid during the creation were used as basis. See Section 10.*
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed. Wash hands before breaks and at the end of work.
- Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

- · Material of gloves
- Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Pasty Light brown Color: **Odorless** · Odor: Not determined. · Odor threshold: · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. (Contd. on page 5)

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible			
Boiling point/Boiling range:	253 °C (487.4 °F)	(Contd. of page 4)	
Flash point:	>185 °C (>365 °F)		
· Flammability (solid, gaseous):	Not applicable.		
• Decomposition temperature:	Not determined.		
· Ignition temperature:	Product is not selfigniting.		
Danger of explosion:	Product does not present an explosion hazard.		
· Explosion limits: Lower: Upper:	Not determined. Not determined.		
· Vapor pressure:	Not determined.		
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	1.8 g/cm³ (15.021 lbs/gal) (EN ISO 2811-1) Not determined. Not determined. Not determined.		
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.		
· Partition coefficient (n-octanol/water): Not determined.			
 Viscosity: Dynamic at 20 °C (68 °F): Kinematic: Organic solvents: 	80,000 mPas (ISO 2555) Not determined. 0.1 %		
VOC content:	0.1 %		
Solids content:	95.0 % (DIN EN 827.8.2)		
• Other information	No further relevant information available.		

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.

• *Conditions to avoid* No further relevant information available.

• *Incompatible materials:* No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

· Additional information: Product releases low quantities of methanol during appropriated application.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

Oral LD50 3,700 mg/kg (rat)

(Contd. on page 6)



Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible

(Contd. of page 5)

Dermal LD50 3,170 mg/kg (rat) • **Primary irritant effect:**

• on the eye: Based on available data, the classification criteria are not met.

• Additional toxicological information: When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

- · IARC (International Agency for Research on Cancer)
- None of the ingredients is listed.

·<u>NTP (National Toxicology Program)</u>

None of the ingredients is listed.

• OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

52829-07-9 Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate

NOEC/21d (static) 0.23 mg/l (Daphnia magna) (OECD RL 211)

- LC50/96h 4.4 mg/l (Leuciscus macrochirus) (OECD RL 203)
- EC50/48h 8.6 mg/l (Daphnia magna) (OECD RL 202 Tl)
- *EC50/3h* >100 mg/l (sludge) (*OECD RL 209*)

EC50/72h 0.705 mg/l (Scenedesmus subspicatus) (RL 92/69/EWG, C.3)

· Persistence and degradability No further relevant information available.

Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

• *Mobility in soil* No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

(Contd. on page 7)





Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible

· Uncleaned packagings:

• *Recommendation: Disposal must be made according to official regulations.*

Transport information	
· UN-Number	
• DOT, ADR, ADN, IMDG, IATA • UN proper shipping name	Void
• DOT, ADR, ADN, IMDG, IATA • Transport hazard class(es)	Void
DOT, ADR, ADN, IMDG, IATA	
Class	Void
Packing group DOT, ADR, IMDG, IATA Environmental hazards:	Void
Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
DOT	
Remarks:	not regulated
ADR	
Remarks:	not regulated
IMDG	
Remarks:	not regulated
· IATA	
Remarks:	not regulated
UN "Model Regulation":	Void

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

All ingredients are listed or are not required to be listed on the TSCA inventory.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 8)



(Contd. of page 6)

⁻US-

Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible

(Contd. of page 7)

- Chemicals known to cause reproductive toxicity for females:
- None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:
- None of the ingredients is listed.
- Chemicals known to cause developmental toxicity:
- None of the ingredients is listed.
- New Jersey Right-to-Know List: 1317-65-3 limestone
- New Jersey Special Hazardous Substance List:
- None of the ingredients is listed.
- Pennsylvania Right-to-Know List:
- 1317-65-3 limestone
- · Pennsylvania Special Hazardous Substance List:
- None of the ingredients is listed.
- GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labeling:
- Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate
- · Hazard statements

Suspected of damaging fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. IF exposed or concerned: Get medical advice/attention. Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

- · *VOC*:
- VOC (EU) 1.1 g/l
- VOC (USA): 1.1 g/l / 0.01 lb/gal
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H227 Combustible liquid.

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H361 Suspected of damaging fertility or the unborn child.

(Contd. on page 9)



US



Printing date 10/25/2023

Reviewed on 10/25/2023

Trade name: WAKOL MS 230 Wood Flooring Adhesive, flexible

(Contd. of page 8)

Contact:	
Date of preparation / last revision 10/25/2023	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Conce	rning the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flammable Liquids 4: Flammable liquids – Category 4	
Skin Irritation 2: Skin corrosion/irritation – Category 2	
Eye Damage 1: Serious eye damage/eye irritation – Category 1	
Toxic to Reproduction 2: Reproductive toxicity – Category 2	

