

Printing date 10/25/2023 Reviewed on 10/25/2023

1 Identification

- · Product identifier
- · Trade name: WAKOL PU 225 Wood Flooring Adhesive A
- · Application of the substance / the mixture Adhesives
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Loba-Wakol, LLC 2732 Hwy 74 West Wadesboro, NC 28170, USA info@loba-wakol.com +1 704 527 5919

- · Information department: Product safety department.
- · Emergency telephone number:

Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or

International (001) 352 323 3500

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0
 Fire = 1
 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Adhesive

· Dangerous components: Void

- US



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive A

(Contd. of page 1)

4 First-aid measures

- Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:

471-34-1 calcium carbonate: 45 mg/m³

PAC-2:

471-34-1 calcium carbonate: 210 mg/m³

PAC-3:

471-34-1 calcium carbonate: 1,300 mg/m³

7 Handling and storage

- \cdot Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.

(Contd. on page 3)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive A

(Contd. of page 2)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

· Body protection: Protective work clothing

US



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive A

(Contd. of page 3)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty
Color: Light beige

Odor: Weak, characteristic
 Odor threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

Flash point:
Flammability (solid, gaseous):

Decomposition temperature:

Undetermined.

421 °C (789.8 °F)

755 °C (491 °F)

Not applicable.

Not determined.

• Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

Vapor pressure: Not determined.

• **Density at 20 °C (68 °F):** 1.67 g/cm³ (13.936 lbs/gal) (EN ISO 2811-1)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 180,000 mPas (ISO 2555)

Kinematic: Not determined.

VOC content: 0.00 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 5)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive A

(Contd. of page 4)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the eye: Based on available data, the classification criteria are not met.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

1318-02-1 zeolites: 3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

- HS



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive A

(Contd. of page 5)

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

· UN proper shipping name

· DOT, ADR, IMDG, IATA Void

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Void

· Packing group

· DOT, ADR, IMDG, IATA Void

Environmental hazards: Not applicable.
 Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information: Not dangerous according to the above specifications.

Void

 $\cdot DOT$

· Remarks: not regulated

 $\cdot ADR$

• Remarks: not regulated

 \cdot *IMDG*

· Remarks: not regulated

 \cdot IATA

· Remarks: not regulated

· UN "Model Regulation": Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed or are not required to be listed on the TSCA inventory.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 7)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive A

(Contd. of page 6)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

None of the ingredients is listed.

· New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

· Pennsylvania Right-to-Know List:

None of the ingredients is listed.

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · National regulations:
- · VOC:
- · VOC (EU) 0.0 g/l
- · VOC (USA): 0.0 g/l / 0.00 lb/gal
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 10/25/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

- HS



Printing date 10/25/2023 Reviewed on 10/25/2023

1 Identification

- · Product identifier
- · Trade name: WAKOL PU 225 Wood Flooring Adhesive B
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Loba-Wakol, LLC

2732 Hwy 74 West

Wadesboro, NC 28170, USA

info@loba-wakol.com

+1 704 527 5919

- · Information department: Product safety department.
- · Emergency telephone number:

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 98229: (USA domestic) 1 800 535 5053 or

International (001) 352 323 3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Sensitization - Respiratory 1 H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Carcinogenicity 2 H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.
Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07

· **Signal word** Danger

· Hazard-determining components of labeling: diphenylmethanediisocyanate, isomeres and homologues

(Contd. on page 2)



Reviewed on 10/25/2023 Printing date 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 1)

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*2 *Health* = *2

Fire = 1

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Adhesive
- · Dangerous components:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

>50-<100%

🗞 Sensitization - Respiratory 1, H334; Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2Å, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 2)

4 First-aid measures

- Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Do not allow product to reach sewage system or any water course.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues: 0.15 mg/m³

(Contd. on page 4)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 3)

· *PAC-2*:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues: 3.6 mg/m³

· PAC-3:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues: 22 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Recommended filter device for short term use: Combination filter A-P2
- Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves Nitrile rubber, NBR

(Contd. on page 5)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 4)

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Color:
Glor:
Glor:
Glor:
Glor:
Glorethreshold:
Fluid
Brown
Characteristic
Not determined.
Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

Flash point:
Flammability (solid, gaseous):

10 °C (50 °F)
>300 °C (>572 °F)
>200 °C (>392 °F)

Not applicable.

• Auto igniting: >600 °C (>1,112 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

• Vapor pressure at 20 °C (68 °F): <0.00001 hPa (<0 mm Hg)

• **Density at 20 °C (68 °F):** 1.23 g/cm³ (10.264 lbs/gal) (EN ISO 2811-1)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

(Contd. on page 6)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 5)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 200 mPas (ISO 2555) **Kinematic:** Not determined.

VOC content: 0.00 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

Oral LD50 > 10,000 mg/kg (rat) (OECD RL 401)

Dermal LD50 >9,400 mg/kg (rabbit) (OECD RL 402)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye:

Irritating effect.

Based on available data, the classification criteria are not met.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Sensitizing effect through inhalation is possible with prolonged exposure.

Sensitizing effect by skin contact is possible with prolonged exposure.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: Group 3 Vol 19, Suppl 7 1987

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

LC50/96h >1,000 mg/l (Danio rerio)

LC0/96h >1,000 mg/l (Brachydanio rerio)

EC50/24h > 100 mg/l (bacteriums)

EC50/48h > 1,000 mg/l (Daphnia magna)

EC50/3h > 100 mg/l (sludge) (OECD 209)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Void

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Void

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Void

· Packing group

· **DOT**, **ADR**, **IMDG**, **IATA** Void

(Contd. on page 8)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 7)

Environmental hazards: Not applicable.
 Marine pollutant: Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

 \cdot **DOT**

· Remarks: not regulated

· ADR

· Remarks: not regulated

 \cdot *IMDG*

· Remarks: not regulated

 \cdot IATA

· Remarks: not regulated

· UN "Model Regulation": Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

· TSCA (Toxic Substances Control Act):

All ingredients are listed or are not required to be listed on the TSCA inventory.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

· New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

Pennsylvania Right-to-Know List:

None of the ingredients is listed.

Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

(Contd. on page 9)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 8)

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07

· Signal word Danger

· Hazard-determining components of labeling:

diphenylmethanediisocyanate,isomeres and homologues

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

· National regulations:

- · VOC:
- · **VOC (EU)** 0.0 g/l
- **VOC (USA):** 0.0 g/l / 0.00 lb/gal
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

(Contd. on page 10)



Printing date 10/25/2023 Reviewed on 10/25/2023

Trade name: WAKOL PU 225 Wood Flooring Adhesive B

(Contd. of page 9)

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Contact:
- · Date of preparation / last revision 10/25/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation - Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1 Carcinogenicity 2: Carcinogenicity - Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

 $Specific\ Target\ Organ\ Toxicity\ -\ Repeated\ Exposure\ 2:\ Specific\ target\ organ\ toxicity\ (repeated\ exposure)-Category\ 2$

US-