Win with versatility!



New – first shear-resistant MS-Wood Flooring Adhesive, firm Universal – also for especially critical parquet Safe – no interaction with paints

Practical – 18 months storage stability in new sealed packaging













WAKOL MS 290 Wood Flooring Adhesive, firm for laying modern, shear-resistant parquet

Bonding all parquet and wood types with MS-Technology

WAKOL MS 290 Wood Flooring Adhesive, firm is the first MS-Adhesive in the group of "hard Wood Flooring Adhesive. firms" in accordance with DIN EN 14293. In addition, the requirements of the former DIN 281 for shear resistance are fully complied with.

WAKOL MS 290 Wood Flooring Adhesive, firm is suitable for all parquet and wood types. This also includes such critical laying as 10 mm solid-wood lam parquet, beech, or solid wood planks e.g. of 25 cm thickness.

On account of the high internal strength, the system ensures maximum protection against block tearing.

Interaction with paints ruled out

WAKOL MS 290 Wood Flooring Adhesive, firm is free from plasticising substances, which means that the possibility of interaction with surface sealants caused by the migration of adhesive components is eliminated. WAKOL MS 290 Wood Flooring Adhesive, firm is of course thus included in the "Connected Systems" system guarantee in combination with Loba paints. Insurance protection exists across systems for the joint use of the systems.

Long durability thanks to sealed containers

WAKOL MS 290 Wood Flooring Adhesive, firm is delivered in practical plastic buckets. A compound aluminium foil, firmly sealed with the edge of the container, ensures optimum protection against moisture and safeguards storage stability for at least 18 months.



Hardening in the unopened original container, resulting in material loss and additional work, is thus eliminated. Constant processing properties, in particular good coatability, are ensured throughout the entire storage period.

Benefits of WAKOL MS 290 Wood Flooring Adhesive, firm

- · For all parquet types
- · Very good scoring stability
- · Long open time
- · Fast strength build-up can be sanded after 24 hours
- · Can be easily removed from painted parguet surfaces
- · For flat-lying natural cork flooring and ready-to-lay cork parquet
- · Especially long storage stability 18 months
- · Best emissions class EMICODE EC1 PLUS

Please always observe the product data sheet before processing.





